

MECHAN MAGNASAFE MS6

MS6-11-DC-06M Safety switch, 1 NO+1 NC, 6m cable

- Max. 2 NO safety contact and 1 NC signal contact
- IP67, made of ABS or stainless steel
- Max. current DC: 24 V DC/ 1 A and AC: 230 V AC/ 2 A
- Connecting cable or M12 connector



MMECHAN CONTROLS

PRODUCT DESCRIPTION

The MAGNASAFE MS6 non-contact safety switches are an industry standard, slim-line, space saving design. Encapsulated into red ABS stainless steel housings, the MS6 safety switches are easy to install, tolerant to misalignment. The non-contact operation has a 10 mm switching distance helping to ensure a long and trouble free operating life.

- Max Contacts 2 Safety 1 Auxiliary
- Contact Rating 2Amp 230VAC / 1Amp 24VDC
- Pre-wired 3, 6 or 10 metre (Longer available to order)
- 10mm Switching
- Slim-line ABS Housing, Fully Sealed IP67

SPECIFICATIONS

Safety contact NO	1
Signal contact NC	1
Contact Current Max	1 A
Activation Distance From	10 mm
Activation Distances	28 mm
Material Case	ABS plastic
Material Case IP Class	ABS plastic IP67, IP69K
IP Class	IP67, IP69K
IP Class Temperature range from	IP67, IP69K -25 °C





