

## MECHAN MAGNASAFE MS6

MS6-11-DC-06M

Safety switch, 1 NO+1 NC, 6m cable

- Max. 2 NO safety contact and 1 NC signal contact
- IP67, made of ABS or stainless steel
- Max. current DC: 24 V DC/ 1 A and AC: 230 V AC/ 2 A
- Connecting cable or M12 connector



### PRODUCT DESCRIPTION

The MAGNASAFE MS6 non-contact safety switches are an industry standard, slim-line, space saving design. Encapsulated into red ABS stainless steel housings, the MS6 safety switches are easy to install, tolerant to misalignment. The non-contact operation has a 10 mm switching distance helping to ensure a long and trouble free operating life.

- Max Contacts 2 Safety 1 Auxiliary
- Contact Rating 2Amp 230VAC / 1Amp 24VDC
- Pre-wired 3, 6 or 10 metre (Longer available to order)
- 10mm Switching
- Slim-line ABS Housing, Fully Sealed IP67

### SPECIFICATIONS

Contact Current Max	1 A
Activation Distance From	10 mm
Signal contact NC	1
Activation Distances	28 mm
Safety contact NO	1
Material Case	ABS plastic
IP Class	IP67, IP69K
Temperature range to	55 °C
Temperature range from	-25 °C
B10d	2,0 milj.

