

## IP CAMERAS

ORL0103810

AF-Zoom HD-E IP camera, Alu

- IP69K rated enclosure
- Video stream is accessible via TCP/IP
- Good vibration resistance, G50



### PRODUCT DESCRIPTION

Orlaco AF Zoom HD-E and PTZ HD-E IP cameras are a sturdy 30x optical zoom Ethernet cameras with IP connection. These cameras can be used in a computer network on cranes, vehicles and vessels. The video stream is accessible via TCP/IP and therefore easily integrated into a computer network. Both models are shock and vibration-proof, filled with nitrogen, 100% waterproof, have heated lens glass and provide the best possible image in all conditions. In addition, the cameras have a 0 lux night vision mode and a built-in brightness function for improved view in dark situations.

#### AF Zoom HD-E

The powerful camera, with an overall 30x zoom is available in an aluminium as well as a stainless steel version. You can control the camera via a computer network. Via a network switch multiple Orlaco cameras can be connected to a computer network. The camera images are accessible via the Orlaco SmartView software or via third party video management software (VMS).

#### PTZ HD-E

This powerful 360 degree rotating PTZ camera with an overall 30x zoom is available in an aluminium as well as a stainless steel version. The camera has a 180 degree lifting angle and can rotate 180 degrees to the left and 180 degrees to the right (360 degrees) with a speed of 12.5 degrees per second. You can control the camera via a computer network. Via a network switch multiple Orlaco cameras can be connected to a computer network. The camera images are accessible via the Orlaco SmartView software or via third party video management software (VMS).

## SPECIFICATIONS

<b>Cable length</b>	5000 mm
<b>IP Class</b>	IP68
<b>Material</b>	Anodized aluminum
<b>Supply Voltage DC Max</b>	30 V DC
<b>Supply Voltage DC Min</b>	18 V DC
<b>Temperature range from</b>	-40 °C
<b>Temperature range to</b>	85 °C

