

## SURFACE MOUNTED LUMINAIRE EL/ELN

15070244

ELN280 surface luminaire, turnable, D-DIFF-0-M8-55, IP54



- Tubular design, surface mounted, length 140 - 1120mm
- Anodised aluminium housing, plastic moun. brackets, IP67
- M8 connector
- Acrylic cover
- Color temperature 5700K

### PRODUCT DESCRIPTION

LED Surface Mounted Luminaire ELN fulfils all requirements according to protection type IP54. This luminaire is the advancement of the EL type and shows the consequent improvement in puncto price attractiveness. This ELN type has a latch for locking the body in the supposed direction and is developed to ensure a lean production. New is also the optional daisy chain installation, for this option just get in touch with us. The PMMA coverage stands for a homogenous illumination.

For applications used in machining or food engineering please see our diverse scope of our Surface Mounted Luminaire L. The same applies if you need a focused light instead of diffuse. For this purpose please see our luminaire family LO with optices in 30 or 60 degrees. The 5700K colour temperature ensures a clear view at all versions of this type. The M8 connector achieves a quick and flexible connection.

### SPECIFICATIONS

<b>Colour rendering index</b>	≥80
<b>Colour temperature</b>	5700 K
<b>Height</b>	35,5 mm
<b>IP Class</b>	IP54
<b>Length</b>	315 mm
<b>Lumen</b>	1206 lm
<b>Material Glass</b>	PMMA
<b>Power Consumption</b>	9,4 W
<b>Supply voltage</b>	24 V DC
<b>Supply voltage</b>	24 V AC
<b>Temperature range from</b>	-20 °C
<b>Temperature range to</b>	45 °C
<b>Width</b>	35 mm

