

SURFACE MOUNTED LUMINAIRE FL/FLS

15070149

FLS150 surface luminaire ESGk-0-3M-55



- Flat design, surface mounted, length 150 - 450mm
- Anodised aluminium housing, IP67
- 3m connecting cable or M8 connector
- Diffuse acrylic, diffuse or clear safety glass cover
- Color temperature 4000 or 5700K

PRODUCT DESCRIPTION

Available in four different lengths, our LED surface mounted luminaire FLS boasts an impressively small installation height of just 17,5 mm. Its anodised aluminium housing has an IP67 protection rating, with its flat design and resistance to splashing water and dust ensuring it can withstand any challenges, even close up.

The LED surface mounted luminaire FLS comes with your choice of a 3 metre cable or M8 connector as standard. For the light cover, you can select from diffuse acrylic glass and diffuse single-pane safety glass. There is even a version with clear single-pane safety glass for applications requiring more light.

SPECIFICATIONS

Colour rendering index	≥80
Colour temperature	5700 K
Height	17,5 mm
IP Class	IP67
Length	150 mm
Lumen	804 lm
Material Glass	ESG c
Power Consumption	7 W
Supply voltage	24 V DC
Temperature range from	-20 °C
Temperature range to	45 °C
Width	70 mm