

COMPACT LUMINAIRES

15070132

105 compact luminaire DIFF-0-M8-55

- Compact, yet high performance, length 105 or 185mm
- Anodised aluminium housing, IP67
- 3m connecting cable or M8 connector
- Diffuse acrylic or safety glass cover
- Color temperature 4000 or 5700K






PRODUCT DESCRIPTION

LED compact luminaire really does live up to its name. Small and easy to handle, it can be adapted to suit widely varying requirements, all whilst guaranteeing maximum lighting quality. The anodised aluminium housing has an IP67 protection rating, meaning it is resistant to splashing water and dust. It is also designed to withstand the challenges faced within the toughest of applications.

The LED compact luminaire comes with your choice of a 3 metre cable or M8 connector as standard. For the light cover, you can select from diffuse acrylic glass and single-pane safety glass.

SPECIFICATIONS

Colour rendering index	≥80
Colour temperature	5700 K
Height	17,5 mm
IP Class	IP67
Length	105 mm
Lumen	402 lm
Material Case	Aluminium
Material Glass	PMMA
Power Consumption	3,5 W
Supply voltage	24 V DC
Temperature range from	-20 °C
Temperature range to	45 °C
Width	25 mm



ESG diffus | Single-pane-safety glass diffuse

