

POWER SUPPLY 1-PHASE, 24V DC LOW POWER PIANO SERIES

PIM36.241

Power supply 100-240VAC 24VDC/1.5A NECC2

- Output current between 1.5 A to 3.8 A
- Push-in or screw terminals
- Up to 93.8% efficiency
- Low no-load power losses



PRODUCT DESCRIPTION

The latest and smallest representatives of the PIANO product family are currently the 24V DIN rail power supplies PIM36 (36W), PIM60 (60W) and PIM90 (90W).

Mini power supplies. New space opportunities.

The new PIANO Mini (PIM) power supplies create space in your systems or machines and allow you a more flexible planning. A 90W DIN rail power supply in a 36 x 90 x 91mm (WxHxD) housing is currently unique in the market. The width of the 36W version is only 22.5mm - so literally a thumb's width. This results in completely new space opportunities for you.

Focus on core features.

The most important characteristic of the PIANO devices is their focus on the core features of a power supply: efficiency, lifetime, reliability and size. The very high PULS quality is maintained in each of these features.

An example is the high efficiency of 91.8% (PIM60) and 93.8% (PIM90) at full load and +40°C ambient temperature. This means lower heat losses. It makes the power supplies more durable and reduces your costs for the cooling of your system.

Push-in or screw terminals - you decide.

For the PIM60 and PIM90 you can choose between push-in and screw terminals. The push-in terminals reduce installation time, and are very reliable in environments prone to shock and vibration. In addition, they are ideally suited for robot-assisted wiring processes.

The screw terminals, that accommodate large diameter wires, are still popular in environments with minimal shock and vibration.

Growing power supply family.

With the new PIANO Mini products, PULS now provides a complete, cost-oriented product family in the 36-480W power range.

SPECIFICATIONS

Type Power Supply	AC-DC
Input voltage range	Wide-range
Power Consumption At 120 V AC	0,63 A
Input voltage AC	100-240 V
Input voltage ac min	90 V AC
Input voltage ac max	264 V AC
Number of phases	1

Inrush current at 230 V ac typical	40 A
Power Consumption At 230 V AC	0,38 A
Supply Frequency	50-60 ±6 %
Inrush current at 120 V ac typical	14 A
Power Factor at 120 V AC, full load. Typical	0,53
Power Factor at 230 V AC, full load. Typical	0,46
Ripple. max	50 mV pp
Output voltage min	24 V DC
Power Reduction Of 60 To 70 ° C	0,96 W/°C
Temperature Range Without Derating From	-10 °C
Output voltage	24 V DC
Output voltage max	28 V DC
Effect	36 W
Output Current	1,5 A
Temperature Range Without Derating To	60 °C
Lifetime at 120 V ac, full load and +40 ° C	162000 h
MTBF (IEC 61709) 230 V AC, Maximum Load, 40 ° C	2081000 h
Efficiency At 230 V AC, full load. Typical	90,6 %
Efficiency At 230 V AC. Typical	88,2 %
Lifetime at 230 V ac, full load and +40 ° C	161000 h
Efficiency At 120 V AC, full load. Typical	90,5 %
Weight	0,14 kg
Depth	91 mm
Width	22,5 mm
Height	90 mm
Clamp type	Push in
IP Class	IP20
Hold-up time at 120 V AC, full load. Typical.	37 ms
Series	Piano
Hold-up time at 230 V AC, full load. Typical.	162 ms
Approvals	CB, CE, cULus, NEC Class 2

