

## 1-PHASE FILTERS, FN2080-SERIES

FN2080-1-06  
FILTER. 2-STAGE 1A/1-PHASE. FLAT PIN

- 1-16 A
- DC-400 Hz
- 2-stage
- High differential and common-mode attenuation, good low frequency attenuation



### PRODUCT DESCRIPTION

### SPECIFICATIONS

<b>Approvals</b>	CSA 22.2 N°8 1986, EN60939, IEC60939, UL 1283
<b>Capacitance Cx</b>	0,33 µF
<b>Capacitance Cy</b>	4,7 nF
<b>Connection Thread</b>	Flat plug
<b>Flammability class</b>	UL94-V2
<b>Frequenze</b>	DC-400 Hz
<b>High Potential Test Voltage "Hipot"</b>	P->PE 2000 V AC, 2 s. P->N 1100 V DC, 2 s.
<b>Inductance</b>	22 mH
<b>Leakage Current Per Phase Max</b>	0,734 mA
<b>MTBF (Mil-HB-217F)</b>	1650000 h @ 40° C, 230 V AC
<b>Operating Voltage Max</b>	250 V AC
<b>Rated Current, At 40 ° C</b>	1 A
<b>Resistance</b>	1000 kΩ
<b>Temperature range from</b>	-25 °C
<b>Temperature range to</b>	100 °C
<b>Weight</b>	0,2 kg

# 1 to 6 A types

