

PANEL MOUNT TIMER DIGITAL

Syr-Line Series

GDF1R10MV2

Timer GDF1 Multifunction 11pin Relay 24-240V ac/dc

- Multifunction
- Display of set and current time
- Time range 0.001 - 9999h
- Backlit LCD display



PRODUCT DESCRIPTION

Now we are launching a new series of digital time relays in the Syr-Line series from Crouzet with clear LCD display that has IP66 enclosure in the front.

The current set time and relay status are shown in the display. Time relays have many different functions as well as up and down counting to choose from.

The programming is very simple and can be locked to prevent accidental change. The time interval is adjustable from 0.001 second and up to 9999 hours and has memory function for time counting in case of potential voltage drop.

The time relays are available with one or two alternating relay outputs that can handle the entire 10A and connect into a 11-pin socket, which allows for both panel and bottom mounting.

SPECIFICATIONS

| | |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals | CE, RoHS, UL |
| Breaking capacity | 2500 VA / 300 W |
| Function | A - Delay on energisation, Ac - Timing after closing and opening of control contact, Ad - Delay on energisation (no reset), B - Timing on impulse (one shot), C - Timing after impulse, D - Symmetrical flashing, Di - Symmetrical flashing, H - Timing on energisation - pulse output, L - Asymmetrical flashing, Li - Asymmetrical flashing |
| IP Class Front | IP66 |
| IP Class Housing | IP20 |
| Mounting | 11-pin socket, Panel mount |
| Multifunction | Yes |
| Output | Relay 1 pole C/O |
| Power Consumption | 2.5 VA / 1 W |
| Supply voltage | 24-240V AC/DC |
| Switching Current Max | 10 A |
| Temperature range bearing, from | -30 °C |

| | |
|-------------------------------|------------------|
| Temperature range bearing, to | 70 °C |
| Temperature range from | -10 °C |
| Temperature range to | 60 °C |
| Time Range | 0,001 s - 9999 h |

