

AUDIBLE WARNING BUZZERS

L22VA03L

Baco Buzzer 80dB 18-30V ac/dc

- Buzzer pulse or continuous sound
- IP66 / IP69K
- 80dB at a distance of 10cm
- 30,000h service life



PRODUCT DESCRIPTION

SPECIFICATIONS

| | |
|--|--|
| Approvals | CE, CSA 22.2, IEC 60068-2-3, IEC 60068-2-30, IEC 60068-2-52, IEC 60068-2-6, IEC 60529, IEC 60947-1, IEC 60947-5-1, IEC 62262, UL, UL 508 |
| Climate resistance cyclic damp heat | IEC 60068-2-3 |
| Climate resistance to sea air | IEC 60068-2-52 |
| Climate-resistant heat | IEC 60068-2-30 |
| Color | Black |
| Frequenze | 50/60 Hz |
| Height | 29,7 mm |
| Insulation voltage | 4 kV |
| IP Class | IP20, IP66, IP69, IP69K, NEMA Type 1, NEMA Type 2, NEMA Type 3, NEMA Type 3R, NEMA Type 3S, NEMA Type 4, NEMA Type 4X, NEMA Type 12 |
| Length | 48,8 mm |
| Lifespan Electrical | 30.000 h |
| Power Supply ACDC max | 30 V |
| Power Supply ACDC min | 18 V |
| Protection Class | II |
| Recommended Torque | 3 Nm |
| Sound level | 80 dB |
| Structural Depth | 37,2 mm |
| Temperature range bearing, from | -40 °C |
| Temperature range bearing, to | 85 °C |

Temperature range from -25 °C

Temperature range to 70 °C

Weight 0,02 g

