

## NON ILLUMINATED SELECTOR SWITCH

Long Lever Handle

L21KP01

- IP66 / IP69K
- 2 or 3 position
- Latching or spring return
- Optional lever colours



### PRODUCT DESCRIPTION

Non illuminated selector switch head with a long lever handle that mount in a 22.5mm hole with protection rating IP66 / IP69K. Combine with separate clip and contact blocks to make complete switch assembly.

Standard body colour is grey with a black lever but also available with red, green & grey lever please enquire for more details.

Available in 2 or 3 position, latching or spring return in various switching angles.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

### SPECIFICATIONS

<b>Angle</b>	45°
<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Climate resistance cyclic damp heat</b>	IEC 60068-2-3
<b>Climate resistance to sea air</b>	IEC 60068-2-52
<b>Climate-resistant heat</b>	IEC 60068-2-30
<b>Color</b>	Red
<b>Function</b>	Stable
<b>Illuminated</b>	No
<b>Impact resistance</b>	IK05
<b>IP Class</b>	IP66, IP69, IP69K
<b>Number of positions</b>	2
<b>Protection Class</b>	II (double insulated)
<b>Recommended Torque</b>	3 Nm

Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Long lever
Weight	17,8 g

