

## ILLUMINATED PUSHBUTTON

Super Flush Head

L23AH10  
PUSH-B FLUSH SP-RTN ILL RED

- IP66 / IP69K
- Spring return
- Low profile flush mount
- Illuminate with LED blocks



### PRODUCT DESCRIPTION

Illuminated super flush pushbutton heads that mount in a 30.5mm hole with protection rating IP66 / IP69K. Ideal for applications where a tamper proof, low profile button is required as only protrudes from front of panel by 2.8mm. Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated pushbutton assembly. Available in multiple colours in spring return with a metallic chrome bezel. Optional text or symbol can be added please enquire for more details.

### SPECIFICATIONS

<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Climate resistance cyclic damp heat</b>	IEC 60068-2-3
<b>Climate resistance to sea air</b>	IEC 60068-2-52
<b>Climate-resistant heat</b>	IEC 60068-2-30
<b>Color</b>	Red
<b>Function</b>	Spring return
<b>Illuminated</b>	Yes
<b>Impact resistance</b>	IK05
<b>IP Class</b>	IP66
<b>Recommended Torque</b>	3 Nm
<b>Temperature range bearing, from</b>	-40 °C
<b>Temperature range bearing, to</b>	70 °C
<b>Temperature range from</b>	-25 °C

Temperature range to

70 °C

Type/Model

Super flush pushbutton

