

## ILLUMINATED SELECTOR SWITCH

Long Lever Handle

L21KV30  
SEL-SWITCH ILL 2 POS LONG BLK

- IP66 / IP69K
- 2 or 3 position
- Illuminate with LED blocks
- Black lever with translucent surround



### PRODUCT DESCRIPTION

Illuminated selector switch head with a long lever handle that mount in a 22.5mm hole with protection rating IP66 / IP69K. Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated selector switch assembly.

The central part of the switch head, side and tip of the lever are translucent and illuminate according to the colour of LED block used. The lever of the switch is solid in colour and available only in black.

Available in 2 or 3 position, latching or spring return in various switching angles.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

### SPECIFICATIONS

<b>Angle</b>	45°
<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Climate resistance cyclic damp heat</b>	IEC 60068-2-3
<b>Climate resistance to sea air</b>	IEC 60068-2-52
<b>Climate-resistant heat</b>	IEC 60068-2-30
<b>Color</b>	Black
<b>Function</b>	Stable
<b>Illuminated</b>	Yes
<b>Impact resistance</b>	IK05
<b>IP Class</b>	IP66, IP69, IP69K
<b>Number of positions</b>	2

<b>Protection Class</b>	II (double insulated)
<b>Recommended Torque</b>	3 Nm
<b>Temperature range bearing, from</b>	-40 °C
<b>Temperature range bearing, to</b>	70 °C
<b>Temperature range from</b>	-25 °C
<b>Temperature range to</b>	70 °C
<b>Type/Model</b>	Long lever
<b>Weight</b>	17,8 g

