












PUSHBUTTON ENCLOSURES

LBX0100
BOX EMPTY 1 HOLE GREY LID

- 1, 2, 3, 4 and 5 hole pushbutton enclosures
- Pushbutton enclosure contact blocks



PRODUCT DESCRIPTION

	1 hole	2 holes	3 holes	4 holes	5 holes
					
					
Grey Lid					
Order no.	LBX0100	LBX0200	LBX0300	LBX0400	LBX0500
Yellow Lid					
Order no.	LBX0100J				

PUSHBUTTON ENCLOSURE CONTACTS



Order no.

33S01



33S10



 **Red**

 **Green**

 **Yellow**

 **White**

 **Blue**

24 V AC/DC LED

Order no.	33SARL	33SAGL	33SAYL	33SAWL	33SABL
-----------	--------	--------	--------	--------	--------

130 V AC LED

Order no.	33SARM	33SAGM	33SAYM	33SAWM	33SABM
-----------	--------	--------	--------	--------	--------

230 V AC LED

Order no.	33SARH	33SAGH	33SAYH	33SAWH	33SABH
-----------	--------	--------	--------	--------	--------

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
------------------	------------------------------

Cable entry	2xM16/M20
--------------------	-----------

Climate resistance cyclic damp heat	IEC 60068-2-3
--	---------------

Climate resistance to sea air	IEC 60068-2-52
--------------------------------------	----------------

Climate-resistant heat	IEC 60068-2-30
-------------------------------	----------------

Color enclosure	Grey, Black
------------------------	-------------

Impact resistance	IK07
--------------------------	------

IP Class	IP66
-----------------	------

Protection Class	II
-------------------------	----

Temperature range bearing, from	-40 °C
--	--------

Temperature range bearing, to	70 °C
--------------------------------------	-------

Temperature range from	-25 °C
-------------------------------	--------

Temperature range to	70 °C
-----------------------------	-------

