

ILLUMINATED PUSHBUTTON

Super Flush Head

L23AH10
PUSH-B FLUSH SP-RTN ILL RED

- IP66 / IP69K
- Spring return
- Low profile flush mount
- Illuminate with LED blocks



PRODUCT DESCRIPTION

Illuminated super flush pushbutton heads that mount in a 30.5mm hole with protection rating IP66 / IP69K. Ideal for applications where a tamper proof, low profile button is required as only protrudes from front of panel by 2.8mm. Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated pushbutton assembly. Available in multiple colours in spring return with a metallic chrome bezel. Optional text or symbol can be added please enquire for more details.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Red
Function	Spring return
Illuminated	Yes
Impact resistance	IK05
IP Class	IP66
Recommended Torque	3 Nm
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C

Temperature range to

70 °C

Type/Model

Super flush pushbutton



