

TWIN TOUCH NON FLUSH

Illuminated

L61QK21

TWINPUSH 1-0 GRN-RED PROJ IND

- IP66
- Flush & projecting buttons
- Spring return
- Illuminate with LED blocks



PRODUCT DESCRIPTION

Illuminated flush & projecting twin touch heads that mount in a 22.5mm hole with protection rating IP66

Combine with separate 333E clip, contact blocks & LED module (must be in centre position) to make complete twin touch assembly. The central part of the head is translucent and illuminate according to the colour of LED block used.

Available in various colour / text / symbol combinations.
All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

SPECIFICATIONS

| | |
|--|------------------------------|
| Approvals | UL 508, CSA 22.2, BV, CB, CE |
| Climate resistance cyclic damp heat | IEC 60068-2-3 |
| Climate resistance to sea air | IEC 60068-2-52 |
| Climate-resistant heat | IEC 60068-2-30 |
| Color | Green/red |
| Color Lens | Clear |
| Function | Spring return |
| Illuminated | Yes |
| Impact resistance | IK05 |

| | |
|--|----------------------|
| IP Class | IP66 |
| Recommended Torque | 3 Nm |
| Temperature range bearing, from | -40 °C |
| Temperature range bearing, to | 70 °C |
| Temperature range from | -25 °C |
| Temperature range to | 70 °C |
| Type/Model | Twin touch non-flush |

