

C4 INDUSTRIAL RELAY

4-pole 10 A

C4-A4024A
Relay 14 Pin 4 Pole 24V ac

- Marking system that can be custom-marked at factory
- Colour-coded test button, both lockable and spring-loaded
- Mechanical indication, double windows



PRODUCT DESCRIPTION

SPECIFICATIONS

OFF-Voltage Un Max	0,15
Nominal power ac	2,4 VA
Coil Voltage AC	24 V AC
Surge Current (20Ms)	30 A
Recommended Min Load	10 mA/5 V
Bounce Time	3
Resistive Load 110 V DC Max	55 W
Release Time	8 ms
The Recommended Maximum Load	10 A/250 V AC-1; 0,5 A/110 V DC-1
Breaking Capacity Current	10 A
Release Time Kontaktstudstid	9 ms
Switching Capability Voltage	250 V
Number Of Contacts	4
Contact Material	AgNi
Resistive Load 24 V dc Max	240 W
Frequency	50 Hz

IP Class	IP40
Temperature range bearing, from	-40 °C
Isolation Contact / Coil	2500 V
Insulation Class EN60947	250 V Pollution 3, Group C
Temperature range to	60 °C
Weight	90 g
Temperature range bearing, to	80 °C
Temperature range from	-40 °C
Isolation Contact / Contact	2500 V
Approvals	CCC, Gost R, Lloyd's, CE, RoHS

