

C7 MINIATURE RELAY

2-pole 10 A

C7A2012A
Relay QRC-RELÄ 2-pole 12VAC

- Colour-coded test button, both lockable and non-locking
- Marking system
- Mechanical indication



PRODUCT DESCRIPTION

SPECIFICATIONS

OFF-Voltage Un Max	0,25
Nominal power ac	1,2 VA
Coil Voltage AC	12 V AC
Response Time	16 ms
Working Un	0,8-1,10
Surge Current (20Ms)	30 A
Recommended Min Load	10 mA/10 V
Bounce Time	3
Resistive Load 110 V DC Max	55 W
Release Time	8 ms
The Recommended Maximum Load	10 A/250 V AC-1; 0,5 A/110 V DC-1
Breaking Capacity Current	10 A
Release Time Kontaktstudtid	9 ms
Switching Capability Voltage	250 V
Number Of Contacts	2
Contact Material	AgNi
Resistive Load 24 V dc Max	240 W

Frequency	50 Hz
IP Class	IP40
Temperature range bearing, from	-40 °C
Isolation Contact / Coil	2500 V
Insulation Class EN60947	250 V Pollution 3, Group C
Temperature range to	60 °C
Weight	43 g
Temperature range bearing, to	80 °C
Temperature range from	-40 °C
Isolation Contact / Contact	2500 V
Approvals	CE, Gost R, RoHS, CCC, CSA, Lloyd's, UL

