

## C9 MINIATURE RELAY

4-pole 5 A

C9A4224D

Relay 14 Pin 4 Pole 10 $\mu$  Au 24V dc

- Colour-coded test button, both lockable and non-locking
- Marking system
- Mechanical indication



### PRODUCT DESCRIPTION

### SPECIFICATIONS

OFF-Voltage Un Max	0,25
Nominal power dc	1 W
Coil Voltage DC	24 V DC
Working Un	0,8-1,1
Surge Current (20Ms)	15 A
Recommended Min Load	1 mA/1 V
Resistive Load 110 V DC Max	50 W
Release Time	6 ms
The Recommended Maximum Load	5 A/250V AC-1; 5 A/30 V DC-1
Breaking Capacity Current	5 A
Release Time Kontaktstudtid	7 ms
Switching Capability Voltage	250 V
Number Of Contacts	4
Contact Material	AgNi + 10 $\mu$ Au
Resistive Load 24 V dc Max	100 W
Frequency	50 Hz
IP Class	IP40

Temperature range bearing, from	-40 °C
Isolation Contact / Coil	2000 V
Temperature range to	60 °C
Weight	43 g
Temperature range bearing, to	80 °C
Temperature range from	-40 °C
Isolation Contact / Contact	2500 V
Approvals	CE, Gost R, RoHS, CCC, CSA, Lloyd's, UL

