

C3 INDUSTRIAL RELAY

3-pole 10 A

C3-A3012A
Relay MRC 3-pole 12 VAC

- Colour-coded test button
- Marking system that can be custom-marked at factory
- Mechanical indication, double windows



PRODUCT DESCRIPTION

SPECIFICATIONS

OFF-Voltage Un Max	0,15
Spoleffekt AC	2,2 VA
Coil Voltage AC	12 V AC
Working Un	0,8-1,1
Surge Current (20Ms)	30 A
Recommended Min Load	10 mA/10 V
Resistive Load 110 V DC Max	55 W
Release Time	8 ms
The Recommended Maximum Load	10 A/250 V AC-1; 0,5 A/110 V DC-1
Breaking Capacity Current	10 A
Release Time Kontaktstudstid	9 ms
Switching Capability Voltage	250 V
Number Of Contacts	3
Contact Material	AgNi
Resistive Load 24 V dc Max	240 W

Frequency	50 Hz
IP Class	IP40
Temperature range bearing, from	-40 °C
Isolation Contact / Coil	2500 V
Insulation Class EN60947	250 V, Pollution 3, Group C
Temperature range to	60 °C
Weight	81 g
Temperature range bearing, to	80 °C
Temperature range from	-40 °C
Isolation Contact / Contact	2500 V
Approvals	CE, Gost R, RoHS, CCC, CSA, Lloyd's, UL

