

## POWER SUPPLY 1-PHASE, 5 V DC MINILINE SERIES

ML15.051  
PULS PSU 15W 5-5.5VDC

- Output current 3 A and 5 A
- Up to 80% efficiency
- AC and dc input voltage
- Width of 22.5 mm
- 5 V, 12 V and 24 V DC options



### PRODUCT DESCRIPTION

3 A model included in Pulse series Mini Line 2 is the latest development series of small power supplies with very compact dimensions and low weight. The units have high efficiency, low EMC interference and good protection against mains transients. This makes them useful in almost all electrical environments and are a great addition to the earlier Mini Line series.


Very low quiescent current and high efficiency even at loads down to 60% makes the aggregates at a good energy and environmental choices.

5 A model is included in the earlier series Miniline having a very proven design and spring terminals for the best connection.


For good cooling free space of 40 mm above and 20 mm under the power supply is recommended. The sides 0 mm unless neighbouring products are a heat source, for example, a power supply unit. Leave then a 15 mm air gap

#### Output characteristics

ML15.051 (3 A)



ML30.101 (5A)



## SPECIFICATIONS

Type Power Supply	AC-DC
Input voltage range	Wide-range
Power Consumption At 120 V AC	0,28 A
Input voltage AC	100-240 V
Input voltage ac min	85 V AC

<b>Input voltage dc max</b>	375 V DC
<b>Input voltage DC</b>	110-300 V
<b>Input voltage ac max</b>	264 V AC
<b>Number of phases</b>	1
<b>Inrush current at 230 V ac typical</b>	26 A
<b>Power Consumption At 230 V AC</b>	0,17 A
<b>Supply Frequency</b>	50-60 ±6 %
<b>Inrush current at 120 V ac typical</b>	13 A
<b>Power Factor at 120 V AC, full load. Typical</b>	0,51
<b>Power Factor at 230 V AC, full load. Typical</b>	0,44
<b>Input voltage dc min</b>	88 V DC
<b>Ripple. max</b>	50 mV pp
<b>Output voltage min</b>	5 V DC
<b>Power Reduction Of 60 To 70 ° C</b>	0,4 W/°C
<b>Temperature Range Without Derating From</b>	-10 °C
<b>Output voltage</b>	5 V DC
<b>Output voltage max</b>	5,5 V DC
<b>Effect</b>	15 W
<b>Output Current</b>	3 A
<b>Temperature Range Without Derating To</b>	60 °C
<b>Lifetime at 120 V ac, full load and +40 ° C</b>	70000 h
<b>MTBF (IEC 61709) 230 V AC, Maximum Load, 40 ° C</b>	2686000 h
<b>Efficiency At 230 V AC, full load. Typical</b>	77,2 %
<b>Lifetime at 230 V ac, full load and +40 ° C</b>	93000 h
<b>Efficiency At 120 V AC, full load. Typical</b>	76,8 %
<b>Weight</b>	0,13 kg
<b>Depth</b>	91 mm
<b>Width</b>	22,5 mm
<b>Height</b>	75 mm
<b>Clamp type</b>	Screw on
<b>IP Class</b>	IP20

<b>Hold-up time at 120 V AC, full load. Typical.</b>	45 ms
<b>Series</b>	Miniline
<b>Hold-up time at 230 V AC, full load. Typical.</b>	186 ms
<b>Approvals</b>	ABS, CB, CE, CSA, GL, NEC Class 2, UL
<b>Material Protection</b>	ABS plastic








Fig. 10-1 **Front side**



Fig. 20-1 **Front view**

