



DUAL THERMOSTAT - ZR 011

ZR

01172.0-00

ZR 011 Dual thermostat, 0-60°C, normally open and closed

- Compact
- Separately adjustable max. and min. temperatures
- High breaking capacity



PRODUCT DESCRIPTION

ZR011 is two thermostats in the same casing. One with a breaking contact for regulation of the heater and one with a closing contact for, for example, regulation of the filter fan or activation of overheating protection.

SPECIFICATIONS

| | |
|---------------------------------------|---|
| Approvals | CE, CSA, cULus, EAC, EMC, RoHS, UL E164102, VDE |
| Contact resistance | <10 mΩ |
| Control range temperature from | 0 °C |
| Control range temperature to | 60 °C |
| Depth | 46 mm |
| Flammability class | UL94-V0 |
| Height | 67 mm |
| Humidity Storage | <90% RH |
| Hysteresis Temperature | 7K |
| Inrush Max | 16 A |
| IP Class | IP20 |
| Material of body | Plastic |
| Material Plastic Housing | Plastic |

| | |
|--------------------------------|-----------------|
| Operating Humidity | < 90% RH |
| Operational Temperature | -45°C ... +80°C |
| Storage temperature | -45°C ... +80°C |
| Tolerance for switch on | ±4K |
| Tolerance switch off | ±4K |
| Torque max | 0,5 Nm |
| Weight | 0,09 kg |
| Width | 50 mm |
| Voltage max | 250 V ac |

