

## LCIS ANALOGUE/ANALOGUE CONVERTERS, FIXED

750530.0000

Signal Converter 0-10VDC/0-10VDC 3-vägs

- 6,2mm wide
- Isolation voltage 2,5 kV
- 3-way isolation
- 24 V AC/DC supply
- DNV and GL approved



### PRODUCT DESCRIPTION

The converter features 3-way galvanic isolation, each terminal can be connected by jumper comb. Extremely compact design, width of 6,2mm only. Can be installed in any position. Both push-in and screw terminal versions available.

### SPECIFICATIONS

Approvals	CSA, DNV, UL
Cross Section Max	2,5 mm <sup>2</sup>
Cross section min	0,25 mm <sup>2</sup>
Depth	73 mm
Height	93 mm
Input	330 kΩ
Insulation voltage in/out	2500 V
IP Class	IP20
Linearity	0,05 % FSR
Reaction time	17 ms
Rise Time	6 ms
Supply voltage	24 V AC/DC
Switching Frequency max	30 Hz @ 3 dB

<b>Temperature coefficient</b>	<150 ppm/° K FSR
<b>Temperature range bearing, from</b>	-40 °C
<b>Temperature range bearing, to</b>	80 °C
<b>Temperature range from</b>	-25 °C
<b>Temperature range to</b>	60 °C
<b>Weight</b>	29 g
<b>Width</b>	6,2 mm

