

MOLEX - MPM DIN FORM A LOW HOUSING / HIGH HOUSING

C18209N21

Valve connector Form A, 2P+Earth, Profile Gasket PG9

- With or without LED and transient protection
- Fibreglass-reinforced housing
- Turnable insert
- EN175301-803 (DIN43650)-A



PRODUCT DESCRIPTION

Standard internal thread DIN valve connector, IP65 rated. Available with different thread style, gaskets and circuitry. Conforms to EN 175301-803.

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the PG9 and PG11 internal thread connector cable range. Conforms to EN 175301-803.

SPECIFICATIONS

| | |
|-------------------------------|---------------------|
| Circuit | No circuit |
| IP Class | IP65 |
| Cross-Section Max | 1,5 mm ² |
| Cable Diameter Max | 8 mm |
| Cable Diameter Min | 6 mm |
| Cable entry CVL | PG9 |
| Color House | Black |
| Central Material | Polyamide |
| LED indicator | No |
| Connector | DINA 43650 |
| Temperature range to | 90 °C |
| Temperature range from | -40 °C |
| Current max | 16 A |
| Rated voltage | 250 V AC/300 V DC |

| | |
|-----------------------------|----------------------------|
| Packing Materials | NBR |
| Colour LED | No LED |
| Screw and Gasket | Profile NBR gasket & screw |
| Manufacturer Part No | 1210230238 |

