



T SERIES, MODULAR BEACON, Ø75MM

859501313

TDC AMBER LED STEADY/FLASHING 230VAC

- Ø75mm Modular beacon
- Steady, flashing and Multi-strobe light options
- Wide control voltage range



PRODUCT DESCRIPTION

AUERs T Series range begins with a Ø 75 mm large comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a steady beacon option with BA15d socket for 7 W incandescent bulb, the T Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13 (excluding TNL and TMW+TVS).

There are also optionally available protective vents for pressure balance in harsh weather conditions (humidity, high temperature fluctuations, etc.) for TMW, TMF, TNL. A comprehensive range of selectable mounting options, and an Ingress protection of IP66.

SPECIFICATIONS

Color Lens	Orange
Diameter	75 mm
Flash Frequency	2 Hz
Height	75 mm
IK Class	8
IP Class	IP66
Light source	LED
Light type	Flash
Mounting	Bayonet
Nominal current	66 mA

Nominal Supply Voltage	230-240 V AC
Operational Temperature	-30°C ... 60°C
Terminal connection	2,5 mm ²
Weight	86 g

