



## SIGNAL TOWER MODUL SIGNAL 50 MM

750001900

VLL ORNG WARNG TO 250VAC/DC

- Modular
- IP65 rated
- Temperature range -25 °C...+50 °C



### PRODUCT DESCRIPTION

Modular signal towers consisting of up to 5 modules. Sound module can be installed as is or 1 - 4 signal modules. Signal modules are compatible with a Ba15d or LED light bulb. LED bulbs are highly recommended for demanding environments due to long service life.

The modules are easy to assemble and maintain. A broken light bulb can be changed without having to disassemble the whole tower. The base and the modules are protected so all maintenance procedures can be done even with power switched on. The base includes a 6 pole connector numbered from 0 to 5.

### SPECIFICATIONS

<b>Color House</b>	Black RAL 9005
<b>Color Lens</b>	Orange
<b>Diameter</b>	50 mm
<b>IP Class</b>	IP65
<b>Lamp Socket</b>	B15d
<b>Number Of Optional Modules</b>	5
<b>Operating Voltage AC Max</b>	250 V AC
<b>Operating Voltage AC Min</b>	12 V AC
<b>Supply Voltage</b>	250 V
<b>Supply Voltage DC Min</b>	12 V DC
<b>Temperature range from</b>	-25 °C
<b>Temperature range to</b>	50 °C

**Terminal connection**

2,5 mm<sup>2</sup>

**Weight**

100 g