

## FEED THROUGH TERMINALS - RK 2.5-240MM<sup>2</sup>

RK

1050.2

RK 16 Beige, 16mm<sup>2</sup> feed through, multi-foot

- Screw in cross connectors
- Material polyamide 6.6 - UL94-V2
- Various colour options
- Temperature resistance -40 °C...+105 °C
- Multi-foot TS35/TS32 options



### PRODUCT DESCRIPTION

### SPECIFICATIONS

<b>Approvals</b>	UL, CSA, GL, KEMA KUR, EAC
<b>Color</b>	Beige
<b>Connections</b>	2
<b>Contamination degree</b>	3
<b>Country of origin</b>	CZ
<b>Cross connect channels</b>	1
<b>Cross section single wire from</b>	2,5 mm <sup>2</sup>
<b>Cross section single wire to</b>	25 mm <sup>2</sup>
<b>Cross section stranded wire from</b>	2,5 mm <sup>2</sup>
<b>Cross section stranded wire to</b>	16 mm <sup>2</sup>
<b>Cross section stranded with ferrule from</b>	2,5 mm <sup>2</sup>
<b>Cross section stranded with ferrule to</b>	16 mm <sup>2</sup>
<b>Cross-Section</b>	16 mm <sup>2</sup>
<b>CSA test standard</b>	C22.2 No 158
<b>EAC test standard</b>	TR ZU 004/2011

<b>Flammability class</b>	UL94-V2
<b>GL test standard</b>	IEC 60947-7-1:2002
<b>Height TS 32</b>	63 mm
<b>Height TS 35/7.5</b>	58,5 mm
<b>Insulation Material</b>	Polyamide 6.6
<b>KEMA KEUR test standard</b>	EN 60947-7-1:2009
<b>Length</b>	50 mm
<b>Mounting</b>	TS 35/7,5 and TS 32
<b>Number of levels</b>	1
<b>Operating temperature from</b>	-40 °C
<b>Operating temperature to</b>	105 °C
<b>Overvoltage category</b>	III
<b>Pack Size</b>	50
<b>Plug gauge acc. EN 60 947-1</b>	B7
<b>Rated Current CSA</b>	70 A
<b>Rated Current IEC</b>	76 A
<b>Rated impulse voltage</b>	8 kV
<b>Rated wire cross section from (AWG)</b>	10
<b>Rated wire cross section to (AWG)</b>	6
<b>Rated Voltage IEC</b>	800 V
<b>Screw size</b>	M 5
<b>Screw type</b>	Slotted
<b>Stripping Length</b>	15 mm
<b>Tariff code</b>	85369010
<b>Torque max</b>	4 Nm
<b>Torque Min</b>	2 Nm
<b>Type of terminal</b>	Screw Terminals, DIN Rail terminals
<b>UL test standard</b>	UL 1059
<b>Weight</b>	29,7 g
<b>Width</b>	12 mm
<b>Voltage CSA</b>	600 V

