

## EARTH TERMINALS - ZSL 2.5-16MM<sup>2</sup>

ZSL

3510.2  
ZSL 2,5/2A GNYE

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



### PRODUCT DESCRIPTION

### SPECIFICATIONS

<b>Approvals</b>	UL, CSA, GL, CSA US, cUL, KEMA KUR, EAC
<b>Color</b>	Green/yellow
<b>Connections</b>	2
<b>Contamination degree</b>	3
<b>Country of origin</b>	BG
<b>Cross connect channels</b>	0
<b>Cross section single wire from</b>	0,5 mm <sup>2</sup>
<b>Cross section single wire to</b>	4 mm <sup>2</sup>
<b>Cross section stranded wire from</b>	0,5 mm <sup>2</sup>
<b>Cross section stranded wire to</b>	4 mm <sup>2</sup>
<b>Cross section stranded with ferrule from</b>	0,5 mm <sup>2</sup>
<b>Cross section stranded with ferrule to</b>	2,5 mm <sup>2</sup>
<b>Cross-Section</b>	2,5 mm <sup>2</sup>
<b>CSA test standard</b>	C22.2 No 158
<b>CSAus test standard</b>	UL 1059
<b>cUL test standard</b>	C22.2 No 158
<b>EAC test standard</b>	TR ZU 004/2011
<b>Flammability class</b>	UL94-V0
<b>GL test standard</b>	IEC 60947-7-2:2009
<b>Height TS 35/7.5</b>	39 mm

<b>Insulation Material</b>	Polyamide 6.6
<b>KEMA KEUR test standard</b>	EN 60947-7-2:2009
<b>Length</b>	59 mm
<b>Mounting</b>	TS 35/7,5
<b>Number of levels</b>	1
<b>Number of test pick off options</b>	2
<b>Operating temperature from</b>	-40 °C
<b>Operating temperature to</b>	120 °C
<b>Overvoltage category</b>	III
<b>Pack Size</b>	100
<b>Plug gauge acc. EN 60 947-1</b>	A3
<b>Rated wire cross section from (AWG)</b>	20
<b>Rated wire cross section to (AWG)</b>	12
<b>Stripping Length</b>	10 mm
<b>Tariff code</b>	85369010
<b>UL test standard</b>	UL 1059
<b>Weight</b>	12 g
<b>Width</b>	5,1 mm

