


TRIPLE DECK TERMINALS - ZIKD 2.5MM²

ZIKD

3590.2
ZIKD 2,5 BG

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	UL, CSA, GL, CSA US, cUL, KEMA KUR, EAC
Color	Beige
Connections	3 x 2
Contamination degree	3
Country of origin	CZ
Cross connect channels	3
Cross section single wire from	0,5 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0,5 mm ²
Cross section stranded wire to	4 mm ²
Cross section stranded with ferrule from	0,5 mm ²
Cross section stranded with ferrule to	2,5 mm ²
Cross-Section	2,5 mm ²
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
cUL test standard	C22.2 No 158
EAC test standard	TR ZU 004/2011
Flammability class	UL94-V0

GL test standard	IEC 60947-7-1:2009
Height TS 35/7.5	68 mm
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	116,2 mm
Mounting	TS 35/7,5
Number of levels	3
Number of test pick off options	6
Operating temperature from	-40 °C
Operating temperature to	120 °C
Overvoltage category	III
Pack Size	50
Plug gauge acc. EN 60 947-1	A3
Rated Current CSA	15 A
Rated current CSAus	15 A
Rated current cUL	15 A
Rated Current IEC	24 A
Rated Current To UL	15 A
Rated impulse voltage	6 kV
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	12
Rated voltage CSAus	300 V
Rated voltage cUL	300 V
Rated Voltage IEC	500 V
Rated Voltage To UL	300 V
Stripping Length	10 mm
Tariff code	85369010
UL test standard	UL 1059
Weight	17,37 g
Width	5,1 mm
Voltage CSA	300 V

