


## FEED THROUGH TERMINALS - ZRK 2.5-16 MM<sup>2</sup>

ZRK

3500.1  
ZRK 2.5/2A Green, 2.5mm<sup>2</sup> Tension spring, feed through

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



### PRODUCT DESCRIPTION

### SPECIFICATIONS

Approvals	UL, CSA, GL, CSA US, KEMA KUR, EAC
Color	Green
Connections	2
Contamination degree	3
Country of origin	BG
Cross connect channels	2
Cross section single wire from	0,5 mm <sup>2</sup>
Cross section single wire to	4 mm <sup>2</sup>
Cross section stranded wire from	0,5 mm <sup>2</sup>
Cross section stranded wire to	4 mm <sup>2</sup>

<b>Cross section stranded with ferrule from</b>	0,5 mm <sup>2</sup>
<b>Cross section stranded with ferrule to</b>	2,5 mm <sup>2</sup>
<b>Cross-Section</b>	2,5 mm <sup>2</sup>
<b>CSA test standard</b>	C22.2 No 158
<b>CSAus test standard</b>	UL 1059
<b>EAC test standard</b>	TR ZU 004/2011
<b>Flammability class</b>	UL94-V0
<b>GL test standard</b>	IEC 60947-7-1:2009
<b>Height TS 35/7.5</b>	39 mm
<b>Insulation Material</b>	Polyamide 6.6
<b>KEMA KEUR test standard</b>	EN 60947-7-1:2009
<b>Length</b>	59 mm
<b>Mounting</b>	TS 35/7,5
<b>Number of levels</b>	1
<b>Number of test pick off options</b>	2
<b>Operating temperature from</b>	-40 °C
<b>Operating temperature to</b>	120 °C
<b>Overvoltage category</b>	III
<b>Pack Size</b>	100
<b>Plug gauge acc. EN 60 947-1</b>	A3
<b>Rated Current CSA</b>	27 A
<b>Rated current CSAus</b>	27 A
<b>Rated Current IEC</b>	24 A
<b>Rated Current To UL</b>	27 A
<b>Rated impulse voltage</b>	8 kV
<b>Rated wire cross section from (AWG)</b>	20
<b>Rated wire cross section to (AWG)</b>	12
<b>Rated voltage CSAus</b>	600 V
<b>Rated Voltage IEC</b>	800 V
<b>Rated Voltage To UL</b>	600 V
<b>Stripping Length</b>	10 mm
<b>Tariff code</b>	85369010
<b>Type of terminal</b>	Tension Spring
<b>UL test standard</b>	UL 1059

<b>Weight</b>	7,6 g
<b>Width</b>	5,1 mm
<b>Voltage CSA</b>	600 V

