

SPECIFICATIONS

Additional information	for SRK 4/2A
Approvals	EAC
Color	Beige
Connections	1
Contamination degree	3
Country of origin	DE
Cross section single wire from	0,2 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0,2 mm ²
Cross section stranded wire to	4 mm ²
Cross section stranded with ferrule from	0,2 mm ²
Cross section stranded with ferrule to	2,5 mm ²
Cross-Section	2,5 mm ²
EAC test standard	TR ZU 004/2011
Flammability class	UL94-V0
Height	26,7 mm
Height TS 35/7.5	53 mm
Insulation Material	Polyamide 6.6
Length	37,8 mm
Load Current Max	32 A
Operating temperature from	-40 °C
Operating temperature to	120 °C
Overvoltage category	III
Pack Size	10
Plug gauge acc. EN 60 947-1	A3
Rated Current IEC	24 A
Rated impulse voltage	8 kV
Rated wire cross section from (AWG)	22
Rated wire cross section to (AWG)	12
Rated Voltage IEC	800 V
Screw size	M 2,5

Screw type	Slotted
Stripping Length	10 mm
Tariff code	85369010
Torque max	0,8 Nm
Torque Min	0,4 Nm
Type of terminal	Screw Terminals, DIN Rail terminals
Weight	6,1 g
Width	5,9 mm

