

## LIYY PVC ELECTRONIC CABLE

SAB03050214/04K  
LIYY 2x0,14 mm129



- Color coded according to DIN 47100
- Flexible
- Small outer diameter
- Small bend radius

### PRODUCT DESCRIPTION

LIYY PVC electronic cable is suitable for use in industrial applications such as scales and control panels to transmit measuring, control and voice signals.

### SPECIFICATIONS

<b>Number Of leads</b>	2
<b>Cross-Section</b>	0,14 mm <sup>2</sup>
<b>Material Outer Jacket</b>	PVC
<b>Shielded</b>	No
<b>Nominal Voltage</b>	U <sub>o</sub> /U 0,14 mm <sup>2</sup> = 350 V, ≥ 0,25 mm <sup>2</sup> = 500 V
<b>Diameter Outer -5%</b>	3,3 mm
<b>Temperature Range The Use Of</b>	80 °C
<b>Temperature Range The Use Of</b>	-40 °C
<b>Temperature Range For Flexible Use</b>	80 °C
<b>Temperature Range Flexible Use Of</b>	-5 °C
<b>Copper Weight</b>	2,7 kg/km
<b>Weight</b>	12 kg/km
<b>Core Insulation</b>	PVC
<b>Core identification</b>	Colour Coded
<b>Approvals</b>	REACH, RoHS
<b>Test Voltage</b>	1200 V
<b>Area of application</b>	Flexible use
<b>Colour Outer Sheath</b>	Grey