

## STN-JZ/JB UNSHIELDED LIFT CABLE

KAB012007010/04  
STN-JZ 7G1 mm<sup>2</sup>



- Built-in suspension element
- Neopren sheathed

### PRODUCT DESCRIPTION

STN-JZ/JB can be used in elevators, conveyors and machine tools as control or signal cable. Sheath is made from rubber compound. The cable features a suspension element in the center of the cable for increased tensile strength.

High resistance against oils and chemicals, can be installed in dry, damp or wet conditions in temperatures as low as -30°C.

### SPECIFICATIONS

<b>Copper Weight</b>	72 kg/km
<b>Bending Radius Flexible Use</b>	10 x d
<b>Shielded</b>	No
<b>Diameter Outer -5%</b>	12,9 mm
<b>Core identification</b>	Number Coded
<b>Colour Outer Sheath</b>	Black
<b>Test Voltage</b>	3000 V
<b>Cross-Section</b>	1 mm <sup>2</sup>
<b>Temperature Range The Use Of</b>	-40 °C
<b>Area of application</b>	Flexible use
<b>Material Outer Jacket</b>	Neoprene
<b>Temperature Range Flexible Use Of</b>	-30 °C
<b>Core Insulation</b>	Rubber compound
<b>Bending Radius Fixed Laying</b>	10 x d
<b>Temperature Range For Flexible Use</b>	80 °C
<b>Nominal Voltage</b>	Uo/U 450/750 V
<b>Weight</b>	230 kg/km
<b>Number Of leads</b>	7
<b>Approvals</b>	RoHS