

H05RN-F FINE-STRANDED CABLE

KAB01000207/04K
H05RN-F 2x0,75 mm²



- Rubber cable for connecting electrical appliances
- Suited for low mechanical stress
- Rubber insulation according to DIN VDE 0282 part 4
- Dry, damp and wet areas
- Withstands fat and oils

PRODUCT DESCRIPTION

H05RN-F is a rubber cable suitable for connecting various electrical appliances as well as fixed installations. Suitable for dry, damp and wet environments and areas where the cable comes in contact with fat and oils. Also withstands ozone and low mechanical stress.

SPECIFICATIONS

Copper Weight	14,4 kg/km
Bending Radius Flexible Use	Min. 7,5 x d
Diameter Outer -5%	8,2 mm
Core identification	Colour Coded
Colour Outer Sheath	Black
Test Voltage	2000 V
Cross-Section	0,75 mm ²
Temperature Range The Use Of	-30 °C
Area of application	Flexible use
Material Outer Jacket	Rubber compound
Temperature Range Flexible Use Of	-30 °C
Core Insulation	Rubber compound
Bending Radius Fixed Laying	Min. 7,5 x d
Temperature Range For Flexible Use	60 °C
Nominal Voltage	Uo/U 300/500 V
Weight	63 kg/km
Number Of leads	2
Cable type	Rubber-insulated cable
Approvals	RoHS

RRRC