

H05RR-F FINE-STRANDED CABLE

KAB00900207/04K
H05RR-F 2x0,75 mm²



- Rubber cable for connecting electrical appliances
- Suited for medium mechanical stress
- Rubber insulation according to DIN VDE 0282 part 4
- Household, office and commercial applications

PRODUCT DESCRIPTION

Rubber-insulated H05RR-F is suitable for connecting various household, office and commercial electrical appliances such as vacuums, different kitchen equipment and tools. Withstands medium mechanical stress, applicable also for fixed installations.

SPECIFICATIONS

Copper Weight	14,4 kg/km
Bending Radius Flexible Use	Min. 7,5 x d
Shielded	No
Diameter Outer -5%	6,2 mm
Core identification	Colour Coded
Colour Outer Sheath	Black
Test Voltage	2000 V
Cross-Section	0,75 mm ²
Temperature Range The Use Of	-30 °C
Area of application	Flexible use
Material Outer Jacket	Rubber compound
Temperature Range Flexible Use Of	-30 °C
Core Insulation	Rubber compound
Bending Radius Fixed Laying	Min. 7,5 x d
Temperature Range For Flexible Use	60 °C
Nominal Voltage	Uo/U 300/500 V
Weight	51 kg/km
Number Of leads	2
Cable type	Rubber-insulated cable
Approvals	RoHS

RRRC