



## SABIX®A 200 FRNC HALOGEN-FREE CONTROL CABLE

SAB62000207

A 200 FRNC 2x0,75 mm<sup>2</sup>


- Numbered cores
- No flame propagation
- Flame retardant and self-extinguishing
- Very flexible also in subzero temperatures

### PRODUCT DESCRIPTION

SABIX®A 200 FRNC is a halogen-free control cable most suitable for use in automation systems, car manufacturing industry and railway technologies. The cable is highly flexible, flame retardant and self-extinguishing and it does not propagate flame. Suitable for areas where development of corrosive conflagration gases threatens the safety of people and equipment such as offices and terminals.

### SPECIFICATIONS

<b>Copper Weight</b>	14,4 kg/km
<b>Bending Radius Flexible Use</b>	Min. 6 x d
<b>Shielded</b>	No
<b>Diameter Outer -5%</b>	5,6 mm
<b>Core identification</b>	Number Coded
<b>Test Voltage</b>	3000 V
<b>Cross-Section</b>	0,75 mm <sup>2</sup>
<b>Temperature Range The Use Of</b>	-40 °C
<b>Area of application</b>	Flexible use
<b>Material Outer Jacket</b>	SABIX®
<b>Twister pairs</b>	No
<b>Temperature Range Flexible Use Of</b>	-30 °C
<b>Core Insulation</b>	SABIX®
<b>Bending Radius Fixed Laying</b>	Min. 4 x d
<b>Temperature Range For Flexible Use</b>	85 °C
<b>Nominal Voltage</b>	U <sub>o</sub> /U 300/500 V
<b>Weight</b>	48 kg/km
<b>Number Of leads</b>	2
<b>Color Jacket</b>	Grey RAL 7000

Approvals	RoHS
Halogen	Yes

