

MHK5 ABSOLUTE HOLLOW SHAFT ENCODER

MHK515-PROF-001

Absolute encoder, ø58, ø15, Profibus

- Diameter 58mm, bore 15mm
- Resolution (Max): 13x16 bits
- CANopen, DeviceNet, Ethercat, Ethernet/IP, Interbus, Modbus, Parallel, Profibus, Profinet
- IP64



PRODUCT DESCRIPTION

SPECIFICATIONS

Sensor type	Absolute
Housing diametre	58 mm
Shaft Diameter	15 mm
Resolution	Max. 13 bit resoluutiolle ja 12 bit kierroksille
Connection Thread	Screw terminal
IP Class	IP64
Speed max.	6000 rpm
Supply Voltage DC Min	10 V DC
Supply Voltage DC Max	30 V DC
Temperature range from	-40 °C
Temperature range to	85 °C
Output	Profibus
Version	Multiturn

PROGRAMMABLE PARAMETERS

Operating Parameter	This parameter determines the counting direction, in which the output code increases or decreases. As an important operating parameter the code sequence (complement) can be programmed.
Resolution per turn	Value between 1 and 8192 can be programmed.
Total resolution "Max range"	This parameter is used to program the desired number of measuring units over the total measuring range. This value may not exceed the total resolution of the absolute rotary encoder.
Preset Value	The preset value is the desired position value, which should be reached at a certain physical position of the shaft.
Limit Switch, Min. and Max	Two position values can be programmed as limit switches. By reaching these values one bit of the 32 bit process value is set to high level.
Com	One free programmable com can be set in the total measuring range.

