

## ADVANCED ILLUMINATION - AL150 BALA LIGHTING

Broad Area Linear Array

SERIE-AL150  
AL150 bar light

- Designed to handle a long, wide field with low angle of view
- Available in 25 mm (1 ") increments up to 80"



### PRODUCT DESCRIPTION

Designed for applications that require broad illumination over a wide area, or for applications requiring an even broader field of illumination, utilise 2 BALA bar lights in parallel.

The AL150 bar light series is expandable in 1" increments up to 82".

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 395
- Blue - 470
- Green - 520
- Red - 625, 660
- Infrared - 880
- White - WHI

For enquiries or quotes for sizes and power options not listed here please [contact us](#).

### SPECIFICATIONS

<b>Approvals</b>	CE, RoHS
<b>Feed</b>	C1, C5, IC, I3, I3S, 24
<b>IP Class</b>	IP50
<b>Life Span</b>	50000 h
<b>Temperature range from</b>	0 °C
<b>Temperature range to</b>	60 °C
<b>Wave-Length</b>	WHI, 395, 470, 520, 625, 660, 880

