

LINEAR BACKLIGHT

SERIE-BL193

BL193 linear backlight




PRODUCT DESCRIPTION

Our Medium Intensity Linear Backlights provide rugged construction for demanding environments. Medium intensity illumination with low power input requirements. Multiple wavelengths available with very consistent illumination over the entire active area. Available in 1" (25mm) increments with lengths up to 80.5" (2044mm).

SPECIFICATIONS

| | |
|-------------------------------|------------------------------|
| Approvals | CE, RoHS |
| Feed | C1, C5, IC, I3, I3S, 24, M12 |
| IP Class | IP64 |
| Life Span | 50000 h |
| Temperature range from | 0 °C |
| Temperature range to | 60 °C |
| Wave-Length | WHI, 470, 520, 660, 880 |



DIMENSIONS ARE IN MILLIMETERS (INCHES)

Sampling of Part Numbers/Dimensions

| Part # | Length (mm/Inches) | Part # | Length (mm/Inches) |
|---------|--------------------|---------|--------------------|
| BL19302 | 42.9 (1.69) | BL19322 | 876.0 (34.49) |
| BL19304 | 71.7 (2.82) | BL19324 | 927.0 (36.49) |
| BL19306 | 104.5 (4.11) | BL19326 | 978.0 (38.49) |
| BL19308 | 137.3 (5.39) | BL19328 | 1029.0 (40.49) |
| BL19310 | 170.1 (6.69) | BL19330 | 1080.0 (42.49) |
| BL19312 | 202.9 (8.0) | BL19332 | 1131.0 (44.49) |
| BL19314 | 235.7 (9.3) | BL19334 | 1182.0 (46.49) |
| BL19316 | 268.5 (10.5) | BL19336 | 1233.0 (48.49) |
| BL19318 | 301.3 (11.8) | BL19338 | 1284.0 (50.49) |
| BL19320 | 334.1 (13.1) | BL19340 | 1335.0 (52.49) |
| BL19322 | 366.9 (14.4) | BL19342 | 1386.0 (54.49) |
| BL19324 | 399.7 (15.7) | BL19344 | 1437.0 (56.49) |
| BL19326 | 432.5 (17.0) | BL19346 | 1488.0 (58.49) |
| BL19328 | 465.3 (18.3) | BL19348 | 1539.0 (60.49) |
| BL19330 | 498.1 (19.6) | BL19350 | 1590.0 (62.49) |

Available in increments of 1 inch up to 80 inches.

