

ADVANCED ILLUMINATION - AL295 MICROBRITE

Compact Area Lighting

SERIE-AL295
AL295 bar light



- High-performance compact line light
- Available in 76 mm (3 inch) increments up to 457 mm (18 inches)

PRODUCT DESCRIPTION

The AL295 is part of the Microbrite family of high performance, compact machine vision lights. Outperforming the competition with a high intensity output of 73 kLux at a working distance of 100mm. The AL295 is available in expandable sizes in 3" increments up to 18".

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 365, 375, 385, 395, 405
- Royal blue - 455
- Blue - 470
- Cyan - 505
- Green - 530
- Amber - 590
- Red orange - 625
- Red - 660
- Infrared - 730, 850, 940
- White - WHI

For enquiries or quotes for wavelength and power options not listed here please [contact us](#).

SPECIFICATIONS

Approvals	CE, RoHS
Feed	C1, C5, IC, I3, I3S
IP Class	IP50
Life Span	50000 h

Temperature range from	0 °C
Temperature range to	60 °C
Wave-Length	WHI, 365, 375, 385, 395, 405, 455, 470, 505, 530, 590, 625, 660, 730, 850, 940